

## Accessories



### Tapered Ring Compressor Sleeves

- Machined from Wiseco sleeve forgings to offer the same toughness as Wiseco's forged pistons.
- Hard anodized and Teflon coated for low friction and prolonged wear resistance.
- Sleeves have a smooth radius that tapers down to the specific bore size.
- Compresses the piston rings smoothly and evenly.
- Greatly reduces the difficulty with installing thin high-performance oil rings.

### Ring Compressor Sleeves
















Part No.	Bore Size (mm)	Bore Size (inches)
RCS06550	65.50	2.579
RCS06600	66.00	2.598
RCS06650	66.50	2.618
RCS06700	67.00	2.638
RCS06750	67.50	2.657
RCS06800	68.00	2.677
RCS06900	69.00	2.717
RCS07000	70.00	2.756
RCS07200	72.00	2.835
RCS07300	73.00	2.874
RCS07400	74.00	2.913
RCS07500	75.00	2.953
RCS07600	76.00	2.992
RCS07700	77.00	3.032
RCS07750	77.50	3.051
RCS07800	78.00	3.071
RCS07900	79.00	3.110
RCS08100	81.00	3.189
RCS08150	81.50	3.209
RCS08200	82.00	3.228
RCS08300	83.00	3.268
RCS08400	84.00	3.307

Part No.	Bore Size (mm)	Bore Size (inches)
RCS08450	84.50	3.327
RCS08500	85.00	3.346
RCS08550	85.50	3.366
RCS08600	86.00	3.386
RCS08650	86.50	3.406
RCS08700	87.00	3.425
RCS08750	87.50	3.445
RCS08800	88.00	3.465
RCS08850	88.50	3.484
RCS08900	89.00	3.504
RCS08950	89.50	3.524
RCS09000	90.00	3.543
RCS09050	90.50	3.563
RCS09100	91.00	3.583
RCS09200	92.00	3.622
RCS09250	92.50	3.642
RCS09300	93.00	3.661
RCS09350	93.50	3.681
RCS09400	94.00	3.701
RCS09450	94.50	3.720
RCS09500	95.00	3.740
RCS09550	95.50	3.760

Part No.	Bore Size (mm)	Bore Size (inches)
RCS09600	96.00	3.780
RCS09700	97.00	3.819
RCS09750	97.50	3.839
RCS09800	98.00	3.858
RCS09850	98.50	3.878
RCS09900	99.00	3.898
RCS09950	99.50	3.917
RCS10000	100.00	3.937
RCS10100	101.00	3.976
RCS10200	102.00	4.016
RCS10400	104.00	4.094

### Optional Heavy Duty Piston Pins

Part #	Description	Gram Weight
S707	19mm x 2.500" (.200" wall)	109
S708	20mm x 2.500" (.200" wall)	117
S733	21mm x 2.002" (.225" wall)	108
S709	21mm x 2.500" (.200" wall)	125
S734	22mm x 2.002" (.225" wall)	115
S710	22mm x 2.500" (.200" wall)	132
S729	23mm x 2.500" (.200" wall)	140

	Top Ring	2nd Ring	Oil Ring
<b>VF</b> Ring Set	1.2mm (.047") Alloy steel Phos. coated Chrome faced 	1.5mm (.057") Cast iron Phosphate coat Taper faced 	2mm (.079") 3-piece oil assembly: Stainless stl. flex-vent spac Chrome faced rails 
<b>XC</b> Ring Set	1mm (.039") Alloy steel Ferrox coated Chrome faced 	1.2mm (.047") Cast iron Phosphate coat Taper faced 	2.8mm (.110") 3-piece oil assembly Stainless stl. flex-vent spac Chrome faced rails 
<b>XX</b> Ring Set	1mm (.039") Stainless steel Gas Nitrided barrel faced 	1.2mm (.047") Cast iron Phosphate coat Taper faced Napier hook 	2.8mm (.110") 3-piece oil assembly Stainless stl. flex-vent spac Gas nitrided rails 
<b>GF</b> Ring Set	1.2mm (.047") Alloy steel Ferrox coated Chrome faced 	1.2mm (.047") Cast iron Phosphate coat Taper faced 	3mm (.118") 3-piece oil assembly Stainless stl. flex-vent spac Chrome faced rails 
<b>E</b> Ring Set	2.0mm (.078") Alloy steel Ferrox coated Chrome faced 	2.0mm (.078") Cast iron Phosphate coat Taper faced 	4mm (.157") 3-piece oil assembly Stainless stl. flex-vent spac 

These Brush hones have been specifically designed to clean the surface of the cylinder bore and provide a fresh cross-hatched surface without removing material (which can increase piston to wall clearance and ring end gap).

Always use an ample amount of honing oil to carry away debris. Wash cylinders thoroughly, with hot soapy water, until paper towels remain clean with no signs of discoloration. Then prep cylinders with any anti-rust agent.

### Nylon Soft Hone Brushes

Bore Range (mm)	Bore Range (Inches)	Part No.	Brush Length	Overall Length
45-57mm	1.77"-2.24"	W6075	2"	10"
57-70mm	2.24"-2.76"	W6076	3"	10"
63-76mm	2.48"-2.99"	W6077	4"	14"
76-89mm	2.99"-3.50"	W6078	4"	14"
89-102mm	3.50"-4.02"	W6079	4"	14"

